

# TECHNICAL SPECIFICATION

Compact industrial computer / IoT gateway

**AG-1621**



## Features

- Cortex-A7 quad core
- 4G LTE, LAN and connectivity
- GNSS
- Debian, OpenWRT Linux support
- Opto-isolated RS485 and RS232
- USB host
- 2 opto-isolated digital inputs
- 1 potential free relay output
- HDMI display support
- Wide power supply range
- DIN rail mounting
- Aluminium enclosure

Small size multipurpose Industrial IoT Gateway/ Industrial Computer based on four core powerful ARM processor. For edge computing working on Debian and also support OpenWRT. In Debian, under the control of

the NodeRED system, it gives unlimited possibilities for easy creation of gateway operation logic. It also has a 4G LTE cellular modem. It has LAN, has opto-isolated RS485, RS232, two digital inputs and one relay output.

Description	Specification
<b>Processor</b>	
Type	ARM Cortex-A7
Number of cores	Quad core
Clock	Up to 960Mhz
<b>RAM Memory</b>	
Memory size	512MB DDR3
Memory speed	1066MHz maximum
<b>Storage</b>	
Internal memory	8, 16 or 32GB eMMC
SD card	One microSD card slot (up to 256Gb)
<b>Graphics</b>	
HDMI	1.4, resolution up to 720P
<b>USB</b>	
USB port number	1
USB type	USB 2.0, host with storage support
Connector	USB type A

Description	Specification
Protection	IEC 61000-4-2 level 4: - 15 kV (air discharge) - 8 kV (contact discharge)
USB overload	600mA
<b>Serial RS485</b>	
Port number	1
Interface Type	RS485
Data Rate	1200 bps ~ 460800 bps
Signals	A and B
Connector	Pluggable screw socket
	Opto-isolated 1.5kV RMS per UL 1577
Protection	IEC 61000-4-2 level 4: - 15 kV (air discharge) - 8 kV (contact discharge) Fail-safe receiver for bus open, short and idle

Description	Specification
<b>Serial RS232</b>	
Port number	1
Interface Type	RS485
Data Rate	200bps ~ 921600bps
Signals	RX, TX, RTS, CTS
Connector	Pluggable screw socket
Protection	Opto-isolated 1.5kV RMS per UL 1577
	IEC 61000-4-2 level 4:
	– 15 kV (air discharge)
	– 8 kV (contact discharge)
	Fail-safe receiver for bus open, short and idle
<b>Ethernet</b>	
Port number	1
Type	10/100M
Ethernet connector	RJ45 with LED indicators
PoE	PoE (spare pare)
<b>Cellular Modem<sup>1</sup></b>	
Cellular bands	Refer cellular specification chart
SIM card	MicroSIM, push-pull type
	3V/1.8V
Antenna connector	SMA female
<b>GNSS<sup>2</sup></b>	
GNSS systems	GPS, BDS, Galileo, GLONASS, QZSS
Antenna connector	SMA female
<b>Digital Inputs</b>	
Input number	2
Input type	Opto-isolated 2.5kV
Configuration	Common IN-GND
Connector	Pluggable screw socket
Max $v_{in}$	30V DC
Logic 1 Voltage	3.5V to max $v_{in}$
<b>Digital Output</b>	
Output number	1
Output type	Relay, NO (normal open)
Load <sub>max</sub>	3A230VACor3A30VDC
Connector	Pluggable screw socket
<b>System Functions Indicators</b>	
Indicators	ACT – activity (dual color)
<b>System</b>	
Operating systems	Linux Debian
	OpenWRT
Booting source	lbuilt eMMC memory
	microSD

<sup>1</sup> Apply to LT models. Refer ordering chart and cellular modem specification chart.

<sup>2</sup> Apply to LT models.

Description	Specification
<b>Applications</b>	
Language support	C, Python, Java and all supported by Linux
Local logic apps	NodeRED (on Debian)
	Any other custom app
Web interface	Luci app in OpenWRT
	Webmin in Debian
	Any other custom made
<b>Power Supply</b>	
Power supply	8-36V DC
Power consumption	Average 6W
Connector	3 pin (+, -, earthing) pluggable screw socket
PoE	Passive PoE over spare pairs. Not compatible with IEEE802.3af
Protection	Reverse polarity, surge, over Voltage
<b>Physical Characteristics</b>	
Installation	DIN-Rail, clamp
Housing	Aluminium
Weight	240g approx
Dimensions	88mm x 87mm x 35mm
<b>Environmental Specification</b>	
Operating temp.	-20 ~ 85°C (-4 ~ 185°F)
Storage temp.	-40 ~ 85°C (-40 ~ 185°F)
Ambient RH	5% ~ 95% (non-condensing)

## Gateway



## Standard model list

Standard gateway models that are in regular production. If you have requirements for a different configuration, then select a specific specification from the table "Table with model structure for ordering".

Model	Hardware Options					More information
	Memory	RAM	Cellular Network			
			GB	GB	GPRS	
AG-1621	8GB	512				Without cellular
AG-1621-8G-LT-EU	8GB	512	✓			For India and EU
AG-1621-8G-LT-GL	8GB	512	✓	✓	✓	Global model

## Cellular modem specification of EU (Europe and India) version

EU version of gateway	Cellular network interface details	
<b>Band LTE FTD</b>	B1/3/5/7/8/20/28	
<b>Band LTE TDD</b>	B38/ 40/ 41	
<b>Band GSM</b>	B2/3/5/8 (900/1800MHz)	
<b>GPRS slot</b>	Multi-slot class 12/10	
<b>Bandwidth</b>	1.4/ 3/ 5/ 10/ 15/ 20 MHz	
<b>Output power</b>	LTE-FDD	Class 3 (23 dBm ±2 dB)
	LTE-TDD	Class 3 (23 dBm ±2 dB)
	EGSM900	Class 4 (33 dBm ±2 dB)
	DCS1800	Class 1 (30 dBm ±2 dB)
<b>Maximum data rate</b>	LTE-FDD	10 Mbps (DL)/ 5 Mbps (UL)
	LTE-TDD	8.96 Mbps (DL)/ 3.1 Mbps (UL)
	GSM	85.6 kbps (DL)/ 85.6 kbps (UL)
<b>Power</b>	Compliant to GSM phase 2/2+	
	– Class 4 (2 W 900MHz)	
	– Class 1 (1 W 1800MHz)	

## Cellular modem specification of GL (global) version

GL version of gateway	Cellular network interface details	
<b>Band LTE FTD</b>	B1/B2/B3/B4/B5/B7/B8/B12/B13/B18/B19/B20/B25/B26/B28	
<b>Band LTE TDD</b>	B38/B39/B40/B41	
<b>Band WCDMA</b>	B1/B2/B4/B5/B6/B8/B19	
<b>Band GSM</b>	B2/B3/B5/B8	
<b>Output power</b>	GSM850	Class 4 (33 dBm ±2 dB)
	EGSM900	Class 4 (33 dBm ±2 dB)
	DCS1800	Class 1 (30 dBm ±2 dB)
	PCS1900	Class 1 (30 dBm ±2 dB)
	GSM850 8-PSK	Class E2 (27 dBm ±3 dB)
	EGSM900 8-PSK	Class E2 (27 dBm ±3 dB)
	DCS1800 8-PSK	Class E2 (26 dBm ±3 dB)
	PCS1900 8-PSK	Class E2 (26 dBm ±3 dB)
	WCDMA	Class 3 (24 dBm +1/-3 dB)
	LTE-FDD	Class 3 (23 dBm ±2 dB)

	LTE-TDD	Class 3 (23 dBm ±2 dB)
<b>Maximum data rate LTE</b>	LTE-FDD	150 Mbps (DL)/Max. 50 Mbps (UL)
	LTE-TDD	130 Mbps (DL)/Max. 30 Mbps (UL)
<b>Maximum data rate UMTS</b>	DC-HSDPA	42 Mbps (DL)
	HSUPA	5.76 Mbps (UL)
	WCDMA	384 kbps (DL)/Max. 384 kbps (UL)
<b>Maximum data rate GSM</b>	EDGE	296 kbps (DL)/Max. 236.8 kbps (UL)
	GPRS	107 kbps (DL)/Max. 85.6 kbps (UL)

### Table with model structure for ordering

This table is applicable when ordering larger quantities of gateways and to optimize the selection of certain components. Standard specifications are in the table of standard models.

Model Structure	
<b>Model example</b>	<b>AG-1621- 8G- LT- EU- DEB</b>
<b>Base model name</b>	
AG-1621	
<b>Internal memory</b>	
8G, 16G, 32G, 64G (eMMC)	
<b>Cellular modem</b>	
LT (cellular modem present)	
<b>Cellular regional information</b>	
EU (cellular modem for India and Europe) GL (global cellular modem)	
<b>Pre-installed OS</b>	
DEB – Debian WRT – OpenWRT	

**For more details  
scan or click on  
QR code**



### **Copyright**

Copyright © 2024 Atreyo Research and Development LLP. This technical specification is protected under national and international copyright laws. No part of this user manual may be reproduced, distributed, translated, or transmitted in any form or by any means, electronic or mechanical, including photocopying, recording, or storing in any information storage and retrieval system, without the prior written permission of Atreyo Research and Development LLP. Copy or use any part of this specifications is prohibited without the prior written permission from the Atreyo Research and Development LLP.

### **Trademarks**

Atreyo and the Atreyo logo are registered trademarks of Atreyo Research and Development LLP. All other trademarks and copyrights are the property of their respective owners.

### **Disclaimer**

- The information contained in this datasheet is provided "as is" and is subject to change without notice. While every effort has

been made to ensure the accuracy and completeness of the information contained herein, Atreyo Research and Development LLP assumes no responsibility or liability for any errors or omissions.

- Images used in this specification may differ in appearance from the actual product.
- All dimensions mentioned in the drawings are not to scale and are subject to change and update as may be decided by the Atreyo Research and Development LLP.
- Atreyo Research and Development LLP makes no warranties, either express or implied, regarding the contents of this document, including but not limited to the implied warranties of merchantability and fitness for a particular purpose.
- Users of this datasheet should verify the applicability and suitability of the information and procedures to their particular use. Atreyo Research and Development LLP shall not be liable for any damages, including but not limited to direct, indirect, special, incidental, or consequential damages, arising from or related to the use or inability to use this datasheet or the products described herein.
- By using this datasheet, you agree to the terms and conditions stated above.

**Atreyo Research  
& Development LLP**

**+91 9727741417  
info@atreyo.in**

414, Sunrise Mall, Mansi Circle,  
Ahmedabad, Gujarat, India