TECHNICAL SPECIFICATION

ATREYO®
SOLUTIONS THAT SIMPLIFY

Passenger Information System Display | **APIS-160-2M**



Features

- **Two line of text in English, Hindi, Gujarati etc.**
- **7 Colours for each region of display**
- **Supports all font styles**
- **All Indian alphabets support**
- **High brightness**
- **4G LTE and GSM communication**
- **Light weight thin aluminium body**
- **Inbuilt additional clock display**
- **Front maintenance**

The APIS-160-2M is LED display dedicated to Passenger Information System for use in public transport stations. Specially designed for: bus stops, tram stops, metro stations, and rail stations.
APIS-160-2M has unique facility of displaying seven colours, two line of clear visible text. It supports all Indian alphabets and most of the world's alphabets.

The APIS-160-2M is working in real time with server to fetch proper vehicle schedule.
The separate clock make APIS-160-2M more passenger-friendly by displaying accurate time.

Description	Details
Size of displaying area	970×202mm (W × H)
Size of body of display	1080×405×50 mm (W × H × D)
Pitch of pixels	6mm
Display resolution	160 (H) × 32 (V)
Displays colours	RGB 7 colours, day light readable
LED type	SMD PLCC-2
Angle of viewing	120°V, 120°H
Max. viewing distance	50m
Intensity of Light	4000 cdm or more[1]
Line of text	2 line English/Hindi any other Indian languaget
Line height	16 pixels
Graphics	Pictorial and single colour graphics support (any one from 7 colours)

Description	Details
Communication	4G LTE/GPRS or LAN
Communication protocol	TCP/IP
Communication interval	Real time (configurable interval from 1s to 256s)
Configuration	SMS or LAN (inbuilt web-server)
Controller and antenna	Inbuilt in display
Brightness control	Auto-brightness according ambient light or manual
Message for a particular PIS (can be customized)	• Bus No.: The bus route identity • Destination: The destination of route and via stops • Time: estimated time of arrival of the bus at the given bus stop in minutes
Maintenance	Front maintenance
Power supply	90 - 240V AC (inbuilt supply)


1 6000 cdm version also available on special order

Description	Details
Power consumption	Maximum 150W Average 50W
Screen protection	Antiglare UV resistant sheet
Body material	Powder coated aluminium
Environmental specifications	• Operating Temperature: 0 to +70°C • Humidity: 5% to 95% RH

Description	Details
(self compliance)	• Sealing IP65

Display





Standard model list

These are standard models. Other models and variants are also available upon request. Please contact us if you require a custom order.

Model APIS-160-2		More information
APIS-160-2M	Multicolour	RGB LED used
APIS-160-2A	Amber color	Amber LED used
APIS-160-2MA	Combine amber	RGB LEDs are used, but the colour displayed is amber.

For more details scan or click on QR code

Copyright

Copyright © 2026 Atreyo Research and Development Pvt. Ltd.. This technical specification is protected under national and international copyright laws. No part of this user manual may be reproduced, distributed, translated, or transmitted in any form or by any means, electronic or mechanical, including photocopying, recording, or storing in any information storage and retrieval system, without the prior written permission of Atreyo Research and Development Pvt. Ltd. Copy or use any part of this specifications is prohibited without the prior written permission from the Atreyo Research and Development Pvt. Ltd.

Trademarks

Atreyo and the Atreyo logo are registered trademarks of Atreyo Research and Development Pvt. Ltd.
All other trademarks and copyrights are the property of their respective owners.

Disclaimer

- The information contained in this Technical Specification is provided "as is" and is subject to change without notice. While every effort has been made to ensure the accuracy and completeness of the information contained herein, Atreyo Research and Development Pvt. Ltd. assumes no responsibility or liability for any errors or omissions.
- Images used in this specification may differ in appearance from the actual product.
- All dimensions mentioned in the drawings are not to scale and are subject to change and update as may be decided by the Atreyo Research and Development Pvt. Ltd.
- Atreyo Research and Development Pvt. Ltd. makes no warranties, either express or implied, regarding the contents of this document, including but not limited to the implied warranties of merchantability and fitness for a particular purpose.
- Users of this Technical Specification should verify the applicability and suitability of the information and procedures to their particular use. Atreyo Research and Development Pvt. Ltd. shall not be liable for any damages, including but not limited to direct, indirect, special, incidental, or consequential damages, arising from or related to the use or inability to use this Technical Specification or the products described herein.
- By using this Technical Specification, you agree to the terms and conditions stated above. Atreyo Research and Development Pvt. Ltd. has right to make additions, deletions, alterations or amendments as and when it deems fit and proper, without any prior notice.

Atreyo Research & Development Pvt. Ltd.	+91 9727741417 info@atreyo.in	2106, Z2, Thaltej, Ahmedabad, Gujarat, India