

TECHNICAL SPECIFICATION

Ultrasonic Parking Sensor

APSENSE-110U



Features

- Ultrasonic sensing technology
- Low power consumption
- RGB LED + external LED indicator output
- 7 segment display for configuration
- 8-36V power supply
- Configuration by commands from system
- Blue light support for reserved places
- Screw-in fastening system

The APSENSE-110U is sensor of presence of car in the parking place multi-user parking. Sensor is working as part of Parking Management System and it is sending data about car presence.

It is working on Modbus over RS485 and also has capability to drive external light to indicate vacant

place for park car. The external light colour setting and optional blinking are special function. Also from system is possible to make all indicator light blinking for any emergency situation. Support blue light indicators for reserve spaces.

Description	Parameter
Sensor	
Type	Ultrasonic
Frequency	40kHz
Sensing method	Distance detection
Sensing range	0.4m to 4m
Serial interface	
Interface Type	RS485
Data Rate	57600bps
Signals	A and B
Data Length	8 bits
Parity	none
Stop Bits	1, 8
Flow Control	None
Connector	RJ45 common with power or optional pluggable screw connector
Protection	IEC 61000-4-2 level 4:

Description	Parameter
	- 15 kV (air discharge) - 8 kV (contact discharge)
User interface – display	
Type	7 segment, red colour
Brightness	Configurable form system
Off time	Configurable form system and menu
Data to system protocol	
Protocol type	Modbus RTU
Communication type	By device address communication Broadcasting communication
Indicators	
Inbuilt Indicator	5mm LED
Colours supported	Red, green, blue, magenta, yellow, white
Empty colour	Green, flash green, blue, flash blue

Description	Parameter
External lamp	Support of APL-10 model and APL-11
Lamp connector	3 wire pluggable screw connector
External lamp extra functions	Lamp brightness setting
User interface	
Keys	3 push keys
Functions	
Configuration locally	<ul style="list-style-type: none"> • Modbus address • Range of detection • Time of reaction (delay)
Configuration from system by commands	<ul style="list-style-type: none"> • Range of detection • Time of reaction • LED colour for empty (in some application use blue for handicaps people)
Other functions	<ul style="list-style-type: none"> • Restarting devices over MODBUS • Displaying MODBUS address on all devices • Displaying detection range on all devices • Displaying time of reaction on all devices
Special functions	<ul style="list-style-type: none"> • Synchronised blinking yellow colour of all external indicator for emergency use

Description	Parameter
Power supply	
Connector	RJ45 (common with communication lines) or optional pluggable screw connector
Power supply range	8-36V DC
Power consumption (approx)	<ul style="list-style-type: none"> • Display on: 0.60W (24V) • Display off: 0.25W (24V) • Display on and external LED indicator: 0.85W (24V) • Display off and external LED indicator: 0.50W (24V)
Physical characteristics	
Installation	Ceiling or overhead rail
Housing	ABS grey colour
Weight	140g
Dimensions	110 mm diameter
Environmental specification	
Operating temp.	-10 ~ 55°C (-13 ~ 158°F)
Storage temp.	-40 ~ 85°C (-40 ~ 176°F)
Ambient RH	5% ~ 95% (non-condensing)

Ordering selection chart

Model	Hardware Options	
	Connector type	
APSENSE-110U	RJ45	Pluggable screw terminal
APSENSE-110U	✓	✓
APSENSE-110U-RJ	✓	
APSENSE-110U-SCR		✓

**For more details
scan or click on
QR code**



Copyright

Copyright © 2026 Atreyo Research and Development Pvt. Ltd. This technical specification is protected under national and international copyright laws. No part of this user manual may be reproduced, distributed, translated, or transmitted in any form or by any means, electronic or mechanical, including photocopying, recording, or storing in any information storage and retrieval system, without the prior written permission of Atreyo Research and Development Pvt. Ltd. Copy or use any part of this specifications is prohibited without the prior written permission from the Atreyo Research and Development Pvt. Ltd.

Trademarks

Atreyo and the Atreyo logo are registered trademarks of Atreyo Research and Development Pvt. Ltd. All other trademarks and copyrights are the property of their respective owners.

Disclaimer

- The information contained in this Technical Specification is provided "as is" and is subject to change without notice. While every effort has been made to ensure the accuracy and completeness of the information contained herein, Atreyo

Research and Development Pvt. Ltd. assumes no responsibility or liability for any errors or omissions.

- Images used in this specification may differ in appearance from the actual product.
- All dimensions mentioned in the drawings are not to scale and are subject to change and update as may be decided by the Atreyo Research and Development Pvt. Ltd.
- Atreyo Research and Development Pvt. Ltd. makes no warranties, either express or implied, regarding the contents of this document, including but not limited to the implied warranties of merchantability and fitness for a particular purpose.
- Users of this Technical Specification should verify the applicability and suitability of the information and procedures to their particular use. Atreyo Research and Development Pvt. Ltd. shall not be liable for any damages, including but not limited to direct, indirect, special, incidental, or consequential damages, arising from or related to the use or inability to use this Technical Specification or the products described herein.
- By using this Technical Specification, you agree to the terms and conditions stated above. Atreyo Research and Development Pvt. Ltd. has right to make additions, deletions, alterations or amendments as and when it deems fit and proper, without any prior notice.

**Atreyo Research
& Development Pvt. Ltd.**

**+91 9727741417
info@atreyo.in**

414, Sunrise Mall, Mansi Circle,
Ahmedabad, Gujarat, India