

## Features

- Linux system
- Dual ethernet
- Cellular, WiFi and Bluetooth connectivity
- Dual SIM card support
- Inbuilt GNSS
- Opto-isolated dual RS485
- USB host x2
- Advanced routing techniques and support for multiple VPNs
- Fully programmable Linux environment
- Isolated PoE

## Advantages

- Node-RED support for local logic with GUI
- Industrial temperature range
- Inbuilt memory and SD card support
- Opto-isolated serials and I/Os
- Possibility to write your own applications and scripts
- Supports C, Python, Java, NodeJS etc.
- Compatible with multiple industrial protocols
- Integration with Atr

## Applications

- Controlling and monitoring urban infrastructure
- Control of machines
- Monitoring of energy supply systems for solar and grid and water supply
- Monitoring of oil and coal mining machinery

## AG-1629

### Programmable IoT gateway with Quad core ARM processor



## Introduction

Programmable industrial IoT Gateway working on Linux systems. It provides the ability to install custom scripts and use ready-made scripts. Under the control of the NodeRED it gives unlimited possibilities for easy creation of gateway operation logic. It also has an cellular modem with support for 2 SIM cards. It has two LAN, to isolated RS485 interfaces and four opto-isolated I/Os.

## Technical specification

CPU	Quad core Cortex A7 ARM processor
Storage	8GB
Memory	512MB RAM
Cellular	4G LTE, GSM with dual SIM
Ethernet	2 x 10/100 Ethernet
GNSS	GPS, BDS, Galileo, GLONASS, QZSS
WiFi	IEEE 802.11b/g/n (optional)
Serial	2 x RS485 opto-isolated
Input/output	4 x opto-isolated digital input 4 x output
Other	2 x USB host with USB storage support
Power	8-48V DC or 8-70V DC, PoE
Housing	Aluminium with DIN rail mounting option



Documentation



Product page

**Atreyo Research & Development LLP**  
 414, Sunrise Mall  
 Mansi Circle, Vastrapur, Ahmedabad  
 380015, Gujarat, India  
 +91 9737741417  
 sales@atreyo.in

www.atreyo.in