



Features

- Fully programmable Linux environment
- Quad core ARM Cortex A55, 64bit
- Up to 8GB RAM memory
- SSD (optional)
- 4G LTE, GSM or 5G (optional)
- Two 1Gbps Ethernet ports
- WiFi and Bluetooth (optional)
- GNSS
- Two opto-isolated RS485
- CAN (depending on the model)
- One USB 3.0 and two USB 2.0 hosts
- Wide power supply range
- Aluminium enclosure
- DIN rail mounting

The AIC-550 is multipurpose Industrial Computer with inbuilt M.2 SSD storage for data. It is based on quad core ARM Cortex-A55 64bit processor. The computer has 4G LTE/GPRS or 5G cellular modem and optional WiFi or Bluetooth.

This computer in addition to industrial use, due audio out it can be used as a media and video controller in vehicles and at bus stops, railway stations and as information kiosk controller. It also has a USB type-C port for debugging.

Description	Specification
Processor	
Type	ARM Cortex-A55, 64bits
Number of cores	Quad core
Clock	Up to 1.8GHz
RAM memory	
Memory size	2/4/8GB
Memory speed	
Storage	
Internal memory	16/32/64/128GB eMMC
SD card	One microSD card slot (combine with SIM slot)
SSD	One M.2 SATA SSD drive (optional)
USB	

Description	Specification
USB port number	3
USB type	One USB 3.0 and two USB 2.0 hosts
Connector	USB type A
Protection	IEC 61000-4-2 level 4: – 15 kV (air discharge) – 8 kV (contact discharge)
USB overload	500mA
Serial RS485	
Port number	2
Interface Type	RS485
Data Rate	1200bps to 921600bps
Signals	A, B and GND
Connector	Pluggable push-in

Description	Specification
Protection	Opto-isolated 1.5kV RMS per UL 1577
	IEC 61000-4-2 level 4: – 15 kV (air discharge) – 8 kV (contact discharge)
	Fail-safe receiver for bus open, short and idle
Ethernet	
Number	2
Type	2x 10/100/1000Mbps
Ethernet connector	RJ45 with LED indicators
WiFi¹	
WL3	2.4Ghz and 5Ghz band
WL4	2.4Ghz
WL5	2.4Ghz
Antenna connector	SMA female
Bluetooth²	
Bluetooth	Only with WL1 and 2 WiFi module
Cellular modem³	
Cellular bands	Refer cellular specification chart
SIM card	2 x nanoSIM, tray to prevent cards falling out (hybrid SIM slot with micro SD)
	3V/1.8V
Antenna connector	SMA female
GNSS⁴	
GNSS systems	GPS, BDS, Galileo, GLONASS, QZSS
Antenna connector	SMA female
Digital input	
Input number	1
Input type	Opto-isolated, but common ground with power supply
Connector	Pluggable push-in
Max v_{in}	30V DC
Logic 1 voltage	3.5V to max v_{in}
CAN	
Port number	1
Interface type	CAN
Data Rate	
Signals	L, H and GND
Connector	Pluggable push-in
Protection	

1 WiFi is optional. There are 3 different options of WiFi card offered by Atreyo. Refer ordering chart and WiFi card selection chart.

2 Bluetooth is on WiFi card module. Available only with selected WiFi modules.

3 Apply to LT models. Refer ordering and cellular specification chart.

4 Apply to LT models. Refer ordering and cellular specification chart.

Description	Specification
System function indicators	
Indicators	ACT – activity
	Cellular modem
	Function 1 (user configurable)
	Function 2 (user configurable)
	Function 3 (user configurable)
Debug and development	
System debug	C-type USB to UART inbuilt
Reset	Reset push button
Recover	Recover and system load push button
System	
Operating systems	Linux Debian, Ubuntu, OpenWRT OpenWRT
Booting source	Inbuilt eMMC memory
Application	
Language support	C, Python, Java and all supported by Linux
Local logic apps	NodeRED
	Any other custom app
Web interface	Luci in OpenWRT
	Webmin in Debian
	Any other custom made
Power supply	
Power supply	8-48V DC
Power consumption	Average TBD
Connector	Pluggable push-in (+, -, earthing)
Protection	Reverse polarity, over voltage
Physical characteristics	
Installation	DIN-Rail, clamp
Housing	Aluminium
Weight	TBD approx
Dimensions	114mm x 32mm x 104mm
Environmental specification	
Operating temp.	-20 ~ 85°C (-4 ~ 185°F)
Storage temp.	-40 ~ 85°C (-40 ~ 185°F)
Ambient RH	5% ~ 95% (non-condensing)

Computer

Standard model list

Standard computer models that are in regular production. If you have requirements for a different configuration, then select a specific specification from the table "Table with model structure for ordering". In the standard model, the gateway has 4GB RAM, 32GB eMMC, 2 RS485. These parameters are then not mentioned in the standard model number.

Model	Hardware Options								More information
	Memory	RAM	Cellular Network				GNSS	WiFi	
			GB	GB	GPRS	3G			
AIC-550	32GB	4							Without cellular
AIC-550-LT-EU	32GB	4	✓		✓		✓		For India and EU
AIC-550-LT-EU-WL4	32GB	4	✓		✓		✓	✓	For India and EU
AIC-550-LT-GL	32GB	4	✓	✓	✓		✓		Global model
AIC-550-LT-GL-WL4	32GB	4	✓	✓	✓		✓	✓	Global model

WiFi and Bluetooth selection chart

Not all WiFi cards have all features in all operating systems offered. Therefore, before choosing a card, read the information on the documentation page or contact Atreyo.

WiFi option		WiFi specification	Bluetooth	Bluetooth version
WL3	Standard	802.11b/g/n		
	Band	2.4GHz		
	Speed	54Mbps and 150Mbps for IEEE 802.11g and 802.11n OFDM		
	2.4GHz:	ch1 ~ ch14		
	2.4GHz:	ch1 ~ ch14		
WL4	Standard	802.11b/g/n AP/ STA/ AP + STA		
	Band	2.4GHz and 5Ghz		
	Modulation	CCK/ DBPSK/ DQPSK/ BPSK/ QPSK/ 16QAM/ 64QAM		
	Speed	802.11a 54 Mbps 802.11b 11 Mbps 802.11g 54 Mbps 802.11n 150 Mbps		
WL5	Standard	IEEE 802.11 a/b/g/n AP/ STA	✓	V5.2
	Band	2.4GHz and 5Ghz		
	Channel bandwidth	20 MHz/ 40 MHz		
	Speed	802.11a 54 Mbps 802.11b 11 Mbps 802.11g 54 Mbps 802.11n 150 Mbps		
	5.0GHz:	36, 40, 44, 48, 52, 56, 60, 64, 100, 104, 108, 112, 116, 120, 124, 128, 130, 132, 136, 140, 149, 153, 157, 161, 165		

Cellular modem specification of EU (Europe and India) version

EU version of gateway	Cellular network interface details	
Band LTE FTD	B1/3/5/7/8/20/28	
Band LTE TDD	B38/ 40/ 41	
Band GSM	B2/3/5/8 (900/1800MHz)	
GPRS slot	Multi-slot class 12/10	
Bandwidth	1.4/ 3/ 5/ 10/ 15/ 20 MHz	
Output power	LTE-FDD	Class 3 (23 dBm ±2 dB)
	LTE-TDD	Class 3 (23 dBm ±2 dB)
	EGSM900	Class 4 (33 dBm ±2 dB)
	DCS1800	Class 1 (30 dBm ±2 dB)
Maximum data rate	LTE-FDD	10 Mbps (DL)/ 5 Mbps (UL)
	LTE-TDD	8.96 Mbps (DL)/ 3.1 Mbps (UL)
	GSM	85.6 kbps (DL)/ 85.6 kbps (UL)
Power	Compliant to GSM phase 2/2+	
	– Class 4 (2 W 900MHz)	
	– Class 1 (1 W 1800MHz)	

Cellular modem specification of GL (global) version

GL version of gateway	Cellular network interface details	
Band LTE FTD	B1/B2/B3/B4/B5/B7/B8/B12/B13/B18/B19/B20/B25/B26/B28	
Band LTE TDD	B38/B39/B40/B41	
Band WCDMA	B1/B2/B4/B5/B6/B8/B19	
Band GSM	B2/B3/B5/B8	
Output power	GSM850	Class 4 (33 dBm ±2 dB)
	EGSM900	Class 4 (33 dBm ±2 dB)
	DCS1800	Class 1 (30 dBm ±2 dB)
	PCS1900	Class 1 (30 dBm ±2 dB)
	GSM850 8-PSK	Class E2 (27 dBm ±3 dB)
	EGSM900 8-PSK	Class E2 (27 dBm ±3 dB)
	DCS1800 8-PSK	Class E2 (26 dBm ±3 dB)
	PCS1900 8-PSK	Class E2 (26 dBm ±3 dB)
	WCDMA	Class 3 (24 dBm +1/-3 dB)
	LTE-FDD	Class 3 (23 dBm ±2 dB)
	LTE-TDD	Class 3 (23 dBm ±2 dB)
Maximum data rate LTE	LTE-FDD	150 Mbps (DL)/Max. 50 Mbps (UL)
	LTE-TDD	130 Mbps (DL)/Max. 30 Mbps (UL)
Maximum data rate UMTS	DC-HSDPA	42 Mbps (DL)
	HSUPA	5.76 Mbps (UL)
	WCDMA	384 kbps (DL)/Max. 384 kbps (UL)
Maximum data rate GSM	EDGE	296 kbps (DL)/Max. 236.8 kbps (UL)
	GPRS	107 kbps (DL)/Max. 85.6 kbps (UL)

Table with model structure for ordering

This table is applicable when ordering larger quantities of gateways and to optimize the selection of certain components. Standard specifications are in the table of standard models.

Model Structure	
Model example	AIC-550-32G-4G-IS-128-LT-EU-WL4-R41-CA-DEB
Base model name	
AIC-550	
Internal memory	
8G, 16G, 32G, 64G (eMMC)	
RAM memory	
2G, 4G, 8G (size of RAM in GB)	
Internal storage (SSD)	
IS (internal storage M.2 SSD)	
SSD size	
128G, 256G, 480G, 1T, 2T	
Cellular modem	
LT, 5G (cellular modem)	
Cellular regional information	
GL (global cellular modem) EU (cellular modem for India and Europe)	
WiFi version	
WL1 /WL2/WL3/BT1 (refer WiFi/BT selection chart)	
RS485 port number	
R4 + number of ports (1 if CAN is available or 1 or 2 if not)	
CAN	
CA (only one CAN port)	
Pre-installed OS	
DEB – Debian WRT – OpenWRT UBU – Ubuntu	

**For more details
scan or click on
QR code**



Copyright

Copyright © 2026 Atreyo Research and Development LLP. This technical specification is protected under national and international copyright laws. No part of this user manual may be reproduced, distributed, translated, or transmitted in any form or by any means, electronic or mechanical, including photocopying, recording, or storing in any information storage and retrieval system, without the prior written permission of Atreyo Research and Development LLP. Copy or use any part of this specifications is prohibited without the prior written permission from the Atreyo Research and Development LLP.

Trademarks

Atreyo and the Atreyo logo are registered trademarks of Atreyo Research and Development LLP.

All other trademarks and copyrights are the property of their respective owners.

Disclaimer

• The information contained in this datasheet (technical specification) is provided "as is" and is subject to change without notice. While every effort has been made to ensure the accuracy

and completeness of the information contained herein, Atreyo Research and Development LLP assumes no responsibility or liability for any errors or omissions.

- Images used in this specification may differ in appearance from the actual product.
- All dimensions mentioned in the drawings are not to scale and are subject to change and update as may be decided by the Atreyo Research and Development LLP.
- Atreyo Research and Development LLP makes no warranties, either express or implied, regarding the contents of this document, including but not limited to the implied warranties of merchantability and fitness for a particular purpose.
- Users of this datasheet should verify the applicability and suitability of the information and procedures to their particular use. Atreyo Research and Development LLP shall not be liable for any damages, including but not limited to direct, indirect, special, incidental, or consequential damages, arising from or related to the use or inability to use this datasheet or the products described herein.
- By using this datasheet, you agree to the terms and conditions stated above. Atreyo Research and Development LLP reserves rights t to make additions, deletions, alterations or amendments as and when it deems fit and proper, without any prior notice.

**Atreyo Research
& Development LLP**

**+91 9727741417
info@atreyo.in**

414, Sunrise Mall, Mansi Circle,
Ahmedabad, Gujarat, India