


TECHNICAL SPECIFICATION

**3 phase 10W power supply
with phase selector output**

APS-10W-O



Features

- Wide input voltage from 85V to 440V
- Work on 3 phase, 2 phase or single phase
- 24/12/5V DC 10W output
- Short circuit protection
- Over voltage protection
- Selected phase indicator
- DIN rail mounting
- Small size

The APS-10W-O is 3 phase 10W power supply dedicated to use in application that need continue power source for IoT, Industrial controls, gateways, electrical panel controls etc. Work with single phase to 3 phase connection make ideal for critical control equipment.

This model has extra power 230V phase selector output for powering 230V devices like energy meters, etc.

The APS-10W-O is available with 5V, 12V and 24V DC.

Description	Specification
General	
Class	Class II power supply
Efficiency	Approx 82%
Cooling	Free air convection
Power input	
Phase	Three, dual and single phase
Voltage between phase and N	85-440V AC
Voltage between phase and phase	85-400V AC ¹
Connector	4 pin screw terminal block
Protection	Every phase fuse and MOV rating 4500A

Description	Specification
Power input	
No load consumption	TBD
Output	
Output type	DC
Voltage	5/12/24V ²
Power	10W max.
Connector	2 pin screw terminal block
Over-current protection	≥110% I _o , self-recovery
Short circuit protection	Hiccup, continuous, self-recovery and output fuse
ESD protection	15kV

¹ The supply can work without N in delta connection, but only in versions without phase selector

² See model selection chart

Description	Specification
Voltage accuracy	±5.0 %
Line regulation	±1.5 %
Load regulation	±3 %
Phase selector	
Priority setting	Phase A, phase B, phase C
Maximum load	100W
Connector	2 pin screw terminal block
Protection	Fuse
Switching time	200ms
Load type	Not for inductive load
Indicators	
Phase selector	3 LED for selected phase

Description	Specification
	indication
Power ON	1 green LED
Physical characteristics	
Installation	DIN rail
Housing	ABS
Weight	130g
Dimensions	90mm x 75mm x 50mm
Environmental specification	
Operating Temp.	-25 ~ 70°C (-13 ~ 158°F)
Storage Temp.	-40 ~ 85°C (-40 ~ 176°F)
Ambient RH	5% to 95% (non-condensing)

Standard model list

These are models in regular production. Other models are only made on order with a minimum order quantity. Please [contact us](#) if you require a custom order.

Model	Hardware options			Phase selector output	More information
	Output voltage				
	5V	12V	24V		
APS-10W-O-05	✓			✓	
APS-10W-O-12		✓		✓	
APS-10W-O-24			✓	✓	
APS-10W-O-05-NO	✓				
APS-10W-O-12-NO		✓			
APS-10W-O-24-NO			✓		

**For more details
scan or click on
QR code**



Copyright

Copyright © 2026 Atreyo Research and Development Pvt. Ltd. This technical specification is protected under national and international copyright laws. No part of this user manual may be reproduced, distributed, translated, or transmitted in any form or by any means, electronic or mechanical, including photocopying, recording, or storing in any information storage and retrieval system, without the prior written permission of Atreyo Research and Development Pvt. Ltd. Copy or use any part of this specifications is prohibited without the prior written permission from the Atreyo Research and Development Pvt. Ltd.

Trademarks

Atreyo and the Atreyo logo are registered trademarks of Atreyo Research and Development Pvt. Ltd. All other trademarks and copyrights are the property of their respective owners.

Disclaimer

- The information contained in this Technical Specification is provided "as is" and is subject to change without notice. While every effort has been made to ensure the accuracy and completeness of the information contained herein, Atreyo

Research and Development Pvt. Ltd. assumes no responsibility or liability for any errors or omissions.

- Images used in this specification may differ in appearance from the actual product.
- All dimensions mentioned in the drawings are not to scale and are subject to change and update as may be decided by the Atreyo Research and Development Pvt. Ltd.
- Atreyo Research and Development Pvt. Ltd. makes no warranties, either express or implied, regarding the contents of this document, including but not limited to the implied warranties of merchantability and fitness for a particular purpose.
- Users of this Technical Specification should verify the applicability and suitability of the information and procedures to their particular use. Atreyo Research and Development Pvt. Ltd. shall not be liable for any damages, including but not limited to direct, indirect, special, incidental, or consequential damages, arising from or related to the use or inability to use this Technical Specification or the products described herein.
- By using this Technical Specification, you agree to the terms and conditions stated above. Atreyo Research and Development Pvt. Ltd. has right to make additions, deletions, alterations or amendments as and when it deems fit and proper, without any prior notice.

**Atreyo Research
& Development Pvt. Ltd.**

**+91 9727741417
info@atreyo.in**

414, Sunrise Mall, Mansi Circle,
Ahmedabad, Gujarat, India